



BBI Self Drill Screws Preferred Drillers™

“Preferred by professionals”



- ICC-ES Evaluation Report ESR-3231
- Head-Mark on Screw Heads for Quality Control
- Manufactured & Tested to Demanding Standards
- Manufactured by ISO 9001/TS16949 Registered Factory
- All Proferred Drillers Meet or Exceed ASTM C954 and/or ASTM C1513
- Tighter Tolerance Equals less Wobble Factor, Preventing Disengagement Damage to Other Assembly Parts & Effective Torque Delivery to Install for Good Seating
- Color Coded Packaging for Easy Identification
- 50 lb Heavy Duty Cartons w/Gloss Finish. 2-Bits included, (Phillips product only)
- 1 lb & 5 lb Clear Plastic Heavy Duty Pails. 1-Bit included, (Phillips product only)

Difference	Standard Commercial Parts	Proferred Parts
Wobble Test for Phillips Recess	10 or 12 Degree Max	4 Degree Max
Drill Point Angle specified	No	Yes
Core Hardness	32 to 40 HRC	32 to 45 HRC
Surface Hardness	50 to 56 HRC	50 to 62 HRC (513-750HV)
Plating Thickness	3 Microns Min	5 Microns Min
Salt Spray Test	12 - Hours	24 - Hours

Bugle Head Phillips Drywall




Pan Head Phillips




Pan Phillips Framing




K Lath/Modified Truss Phillips



Hex Washer Head No Slot




HWH No Slot with Sealing Washer



Wafer Head Phillips



Wafer Head Phillips with Wings



Trim Head Square Drive



Flat Head Phillips with Wings



BRIGHTON-BEST INTERNATIONAL

